



MATERIAL SAFETY DATA SHEET
LPS® CFC Free®

Revision Date: August 3, 2011

Supersedes: August 24, 2010

Section 1 • Product and Company Identification

Product Name: LPS® CFC Free®

Part Number(s): 03116 (aerosol), 03101, 03105, 03155, C03116 (aerosol), C03101, C03105, C03155

Chemical Name: Isohexane / Isopropanol Mixture

Product Use: An industrial solvent designed to remove a variety of substrates.

Manufacturer Information: LPS Laboratories, 4647 Hugh Howell Road, Tucker, GA, USA 30084
TEL: USA & Canada: 1 800 241-8334
Outside USA and Canada: +1 770 243-8800
FAX: USA & Canada: 1 800 543-1563
Outside USA and Canada: +1 770 243-8899

Emergency Telephone Number: Chemtrec: USA & Canada: 1 800 424-9300
Outside USA and Canada: +1 703 527-3887

Website: <http://www.lpslabs.com>

Section 2 • Hazards Identification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Emergency Overview:

Aerosol: DANGER: Extremely flammable. Contents under pressure. Harmful or fatal if swallowed.

Bulk: DANGER: Extremely flammable. Harmful or fatal if swallowed.

Primary route(s) of entry: Skin and eye contact. Inhalation.

Potential Acute Health Effects:

Eyes: Irritating to eyes.

Skin: Repeated exposure may cause skin dryness or cracking.

Inhalation: Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache.

Ingestion: Product has a low order of acute oral toxicity, but ingestion of large quantities may cause nausea, vomiting, and gastrointestinal irritation. May cause injury if aspirated into lungs.



MATERIAL SAFETY DATA SHEET
LPS® CFC Free®

Revision Date: August 3, 2011

Supersedes: August 24, 2010

Potential Chronic Health Effects:

Carcinogenic Effects: NTP: No IARC: No OSHA: No ACGIH: No

Mutagenic Effects: None

Teratogenic Effects: This material (or component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Target Organs: Prolonged and repeated exposure to n-hexane may cause peripheral neuropathy by damaging peripheral nerve tissue (that of the arms and legs) and result in muscular weakness and loss of sensation. Prolonged and repeated inhalation of high levels of mixed isomers of hexane resulted in kidney damage in male rats. The effects observed are the same as those seen in male rats exposed to other hydrocarbons. The mechanism by which these chemicals cause the characteristic kidney toxicity is unique to the male rat and the kidney effects are not expected to occur in man. Breathing isopropanol vapors has caused damage to the lining of the middle ear in experimental animals. The relevance of this finding to humans is uncertain. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: liver abnormalities, kidney damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: central nervous system effects.

Medical conditions aggravated by exposure:

Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

Signs and Symptoms

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.

Section 3 • Composition / Information on Ingredients

Component	CASRN	Weight Percent
2-Methylpentane	107-83-5	40 - 50%
3-Methylpentane	96-14-0	10 - 20%
2,3-Dimethylbutane	79-29-8	10 - 20%
Isopropanol	67-63-0	10 - 15%
2,2-Dimethylbutane	75-83-2	5 - 15%
Carbon Dioxide (aerosol only)	124-38-9	1 - 5%
n-Hexane	110-54-3	1 - 3%



MATERIAL SAFETY DATA SHEET

LPS® CFC Free®

Revision Date: August 3, 2011

Supersedes: August 24, 2010

Section 4 • First Aid Measures

Eyes:	Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. DO NOT use eye ointment. Seek medical attention immediately.
Skin:	Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. DO NOT use ointments. Seek medical attention if irritation persists.
Inhalation:	Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical attention immediately.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. DO NOT leave victim unattended. Seek medical attention immediately.

Section 5 • Fire Fighting Measures

Products of Combustion:	Carbon monoxide and carbon dioxide.		
General Fire Hazards:	Do not use on energized equipment. High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers.		
Firefighting media:	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use CO ₂ , water spray, fog or foam. Cool containing vessels with water jet in order to prevent pressure build-up, auto-ignition or explosions.		
Sensitivity to Impact:	None	Sensitivity to Static Discharge:	Yes
Protection Clothing (Fire):	Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.		

Special Remarks on Explosion Hazards:

Aerosols may explode upon heating, spread fire and overcome sprinkler systems.

Section 6 • Accidental Release Measures

Containment Procedures:	Small Spill and Leak:	Eliminate ignition sources. Absorb with an inert material and dispose of properly.
	Large Spill and Leak:	Eliminate ignition sources. Secure the area and control access. Dike far ahead of a liquid spill to ensure complete collection. Pick up free liquid for disposal using absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal.
Clean-Up Procedures:	Recover free product and place in a suitable container for disposal.	
Evacuation Procedures:	Ventilate area of leak or spill. Keep unnecessary and unprotected people away.	
Special Procedures:	Remove all sources of ignition. Ventilate area. Wear personal protective equipment during cleanup.	



MATERIAL SAFETY DATA SHEET

LPS® CFC Free®

Revision Date: August 3, 2011

Supersedes: August 24, 2010

Section 7 • Handling and Storage

Handling: DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists.

Storage: Keep container closed and in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F (49°C).

Precautions to be taken in handling and storage:

Store aerosols as Level 3 Aerosol (NFPA 30B). Store bulk liquids as NFPA Class 1B liquid. Store all materials in a dry, well-ventilated area. Avoid breathing vapors. Ground and bond containers before transferring materials.

Section 8 • Exposure Controls / Personal Protection

Exposure Guidelines:

Component	CASRN	OSHA	ACGIH	NIOSH	Supplier
2-Methylpentane	107-83-5	Not established	Not established	100 ppm TWA	500 ppm TLV 1000 ppm STEL
3-Methylpentane	96-14-0	Not established	Not established	100 ppm TWA	500 ppm TLV 1000 ppm STEL
2,3-Dimethylbutane	79-29-8	Not established	Not established	100 ppm TWA	500 ppm TLV 1000 ppm STEL
Isopropanol	67-63-0	400 ppm PEL	200 ppm TLV 400 ppm STEL	400 ppm TWA 500 ppm STEL	400 ppm TWA
2,2-Dimethylbutane	75-83-2	Not established	Not established	100 ppm TWA	500 ppm TLV 1000 ppm STEL
Carbon Dioxide (aerosol only)	124-38-9	5000 ppm PEL	5000 ppm TLV 30000 ppm STEL	5000 ppm TWA 30000 ppm STEL	None reported
n-Hexane	110-54-3	500 ppm PEL	50 ppm TLV	50 ppm TWA	None reported

Engineering Controls: Provide general and/or local exhaust ventilation to keep exposures below the exposure guidelines listed above.

Personal protective equipment

Eye protection: Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and emergency shower facilities are recommended.

Hand protection: Normally no hand protection is required; however, if product will be sprayed for an extended period, "overspray" onto skin may occur. If so, wear chemical resistant gloves conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves.

Respiratory protection: Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed above), use NIOSH approved respiratory protection (i.e. organic vapor cartridge).

General Hygiene Considerations: Wash thoroughly after handling. Have eye-wash facilities immediately available.



MATERIAL SAFETY DATA SHEET
LPS® CFC Free®

Revision Date: August 3, 2011

Supersedes: August 24, 2010

Section 9 • Physical and Chemical Properties

Appearance:	Liquid	Color:	Colorless / water-white
Odor:	Characteristic	Evaporation Rate:	< 1 (Ethyl Ether = 1)
Solubility Description:	< 10% by weight	Flash Point:	< -17°C (+1.4°F) - dispensed liquid
Boiling Point:	60.5°C (141°F) - dispensed liquid	Flash Point Method:	Tag-Closed Cup
Specific Gravity (H₂O=1):	0.64 - 0.67 @ 20°C	Decomposition Temperature:	Not established
Vapor Density (air = 1):	~3	Auto ignition temperature:	306°C (583°F)
Vapor Pressure:	352.53 mm Hg @ 38°C	Flammable limits (estimated):	LOWER: 0.6% UPPER: 7.0%
Rule 1171 PPc:	Not established	Partition Coefficient (octanol/water):	< 1
V.O.C. Content:	Aerosol: 96.2% per State & Federal Consumer Product Regulations; 644 g/L per SCAQMD Rule 102 Bulk: 100% per State & Federal Consumer Product Regulations; 669 g/L per SCAQMD Rule 102	Odor Threshold:	Not established
Melting Point:	Not established	Viscosity:	< 3 cSt @ 25°C
pH:	Not applicable	Volatiles:	100%
Heat of combustion:	Aerosol: > 30 kJ/g Bulk: > 30 kJ/g		

Section 10 • Stability and Reactivity

Chemical Stability:	Product is stable under recommended storage conditions.
Conditions to Avoid:	Keep away from heat and ignition sources.
Incompatibility:	Extremely reactive or incompatible with oxidizing agents.
Hazardous Decomposition:	Combustion will generate smoke, possibly thick and choking, resulting in zero visibility and combustion products include carbon monoxide and carbon dioxide.
Hazardous Polymerization:	Will not occur.



MATERIAL SAFETY DATA SHEET

LPS® CFC Free®

Revision Date: August 3, 2011

Supersedes: August 24, 2010

Section 11 • Toxicological Information

Acute and Chronic Toxicity

A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

B: Component Analysis

Component	CASRN	LC-50	LD-50
2-Methylpentane	107-83-5	> 3125 ppm / rat / 4 hr*	Not established
3-Methylpentane	96-14-0	Not established	Not established
2,3-Dimethylbutane	79-29-8	Not established	Not established
Isopropanol	67-63-0	16000 ppm / rat / 4 hr*	5045 mg/kg / oral / rat*
			5030 - 7900 mg/kg / dermal / rabbit*
2,2-Dimethylbutane	75-83-2	Not established	Not established
Carbon Dioxide (aerosol only)	124-38-9	Not established	Not appropriate
n-Hexane	110-54-3	48000 ppm / rat / 4 hr*	25 g/kg / oral / rat*
			1.3 g/kg / dermal / rabbit*

* Supplier Data

Section 12 • Ecological Information

Mobility: Volatile. Readily absorbed into soil. **Persistence / Degradability:** Only slightly biodegradable

Bioaccumulative potential: Minimal bioaccumulation potential **Other adverse effects:** None known

Ecological studies have not been conducted for this product. The following information is available for component(s) of this product.

Ecotoxicity

Effects on Organisms	Component	CASRN	Test	Species	Results
Acute Toxicity on Fishes	n-Hexane	110-54-3	48-hr LC100	Leuciscus Idus Melanotus	260,000 µg/L
	Isopropanol	67-63-0	24-hr LC50	Carassius Auratus	5,000,000 µg/L
Acute Toxicity on Daphnia	n-Hexane	110-54-3	24-hr LC50	Daphnia Magna	50,000 µg/L
	Isopropanol	67-63-0	24-hr LC50	Daphnia Magna	10,000,000 µg/L
	2-Methylpentane	107-83-5	48-hr EC50	Daphnia Magna	2.1 mg/L
Bacterial Inhibition	No data available				
Growth inhibition of algae	n-Hexane	110-54-3	EC50	Anabaena Inaequalis	1.7%
	Isopropanol	67-63-0	48-hr EC50	Scenedesmus Quadricauda	1,800,000 µg/L
Bioaccumulation in fish	No data available				

* Supplier Data



MATERIAL SAFETY DATA SHEET
LPS® CFC Free®

Revision Date: August 3, 2011

Supersedes: August 24, 2010

Section 13 • Disposal Considerations

Waste Status: Aerosol cans, if depressurized and emptied to less than 1 inch (2.54 cm) of fluid contents, are classified as non-hazardous waste under 40 CFR 261.7 (U.S.). If disposed of in its received form, the aerosol carries the waste codes D001 and D003 (U.S.). Dispensed product, as received, carries the waste codes D001 and D003 (U.S.).

Disposal: Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws and regulations.

Section 14 • Transport Information

Aerosol

D.O.T. Ground	Shipping Name:	Consumer Commodity	UN No.:	NA
	Hazard Class:	ORM-D	Technical Name:	NA
	Subclass:	NA	Hazard Label:	ORM-D Already on box
	Packing Group:	NA		
Road/Rail - ADR/RID	UN No.:	1950	ADR Class:	2.1
	Packing Group:	NA	Classification Code:	5F
	Name and description:	AEROSOLS, flammable	Hazard ID No.:	NA
	Labeling:	2.1	Technical Name:	NA
IMDG-IMO	UN No.:	1950	Class:	2.1
	Shipping Name:	Aerosols	Subsidiary Risk:	NA
	Labeling:	2	Packing Group:	NA
	Packing Instructions:	P003, LP02	EmS:	F-D, S-U
	Marine pollutant:	No	Technical Name:	NA
IATA - ICAO:	UN No.:	1950	Class:	2.1
	Shipping Name:	Aerosols, flammable	Subclass:	NA
	Packing Instructions:	203, Y203 (Ltd. Qty.)	Packing Group:	NA
	Labeling:	Flammable Gas	Technical Name:	NA

Bulk

D.O.T. Ground	Shipping Name:	Flammable Liquid, n.o.s.	UN No.:	1993
	Hazard Class:	3	Technical Name:	Hexanes, Isopropanol
	Subclass:	NA	Hazard Label:	Flammable Liquid
	Packing Group:	NA		
Road/Rail - ADR/RID	UN No.:	1993	ADR Class:	3
	Packing Group:	II	Classification Code:	F1
	Name and description:	Flammable liquid, n.o.s.	Hazard ID No.:	33
	Labeling:	3	Technical Name:	Hexanes, Isopropanol
IMDG-IMO	UN No.:	1993	Class:	3
	Shipping Name:	Flammable liquid, n.o.s.	Subsidiary Risk:	NA
	Labeling:	3	Packing Group:	II
	Packing Instructions:	P001	EmS:	F-E, S-E
	Marine pollutant:	No	Technical Name:	Hexanes, Isopropanol
IATA - ICAO:	UN No.:	1993	Class:	3
	Shipping Name:	Flammable liquid, n.o.s.	Subclass:	NA
	Packing Instructions:	Y341 (Ltd. Qty.), 353, 364 (CAO)	Packing Group:	II
	Labeling:	Flammable Liquid	Technical Name:	Hexanes, Isopropanol

*Note: For air shipment only
 1 gallon (3.78 liter) containers shipped in case quantity (4 to a case), must be shipped via "CARGO AIRCRAFT ONLY" (CAO).
 5 gallon (18.93 liter) containers must be shipped via "CARGO AIRCRAFT ONLY" (CAO).
 55 gallon (208 liter) drums CANNOT be shipped by air.

The preceding information is subject to change and must be verified prior to shipment. It is the responsibility of anyone offering hazardous materials for shipment to ensure compliance with all applicable regulations.



MATERIAL SAFETY DATA SHEET
LPS® CFC Free®

Revision Date: August 3, 2011

Supersedes: August 24, 2010

Section 15 • Regulatory Information

U.S. Federal Regulations

RCRA Hazardous Waste No.: D001, D003

Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA):
n-Hexane 110-54-3 5000 lbs

Toxic Substances Control Act (TSCA):
All components of this product are TSCA inventory listed and/or are exempt.

Superfund Amendments and Reauthorization Act (SARA) Title III SARA Section 311/312 (40 CFR 370) Hazard Categories:
Sudden Release of Pressure (aerosols only), Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372):
n-Hexane 110-54-3 3% max.

Section 112 Hazardous Air Pollutants (HAPs): n-Hexane

State Regulations

California: This product is not labeled for sale in California.

California and OTC States: Aerosol: Not for sale in any jurisdiction adopting CARB or OTC Model rules for consumer products.
Bulk: Not for sale in California. In other jurisdictions, this product is not regulated by consumer product regulations.

New Jersey Right to Know:
Aerosol: 2-Methylpentane 107-83-5 • 3-Methylpentane 96-14-0 • 2,3-Dimethylbutane 79-29-8 • 2,2-Dimethylbutane 75-83-2 • Isopropanol 67-63-0 • n-Hexane 110-54-3 • Carbon Dioxide 124-38-9
Bulk: 2-Methylpentane 107-83-5 • 3-Methylpentane 96-14-0 • 2,3-Dimethylbutane 79-29-8 • 2,2-Dimethylbutane 75-83-2 • Isopropanol 67-63-0 • n-Hexane 110-54-3

International Regulations

Canadian Environmental Protection Act (CEPA):
All of the components of this product are included on the Canadian Domestic Substances list (DSL).

Canadian Workplace Hazardous Materials Information System WHMIS:
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Classification:
Aerosol: Class A, Class B5, Class D2B

WHMIS Classification:
Bulk: Class B2, Class D2B

Other Regulations:
Montreal Protocol listed ingredients: None
Stockholm Convention listed ingredients: None
Rotterdam Convention listed ingredients: None
RoHS Compliant: Yes



MATERIAL SAFETY DATA SHEET
LPS® CFC Free®

Revision Date: August 3, 2011

Supersedes: August 24, 2010

Section 16 • Other Information

MSDS#: 13116 MSDS Preparation Responsible Name: Elena Badiuzzi Compliance Manager Telephone: +1 770 243-8800	HMIS 1996		HMIS III		Health	NFPA Flammability		Reactivity
	Health:	1	Health:	[*] 1				
	Flammability:	3	Flammability Aerosol:	4				
			Flammability Bulk:	3				
	Reactivity:	0	Physical Hazard Aerosol:	2				
			Physical Hazard Bulk:	0			Special	

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Elena Badiuzzi, Compliance Manager
LPS Laboratories, a division of Illinois Tool Works