

MSDS **Material Safety Data Sheet**

From: Avantor Performance Materials, Inc.
Saucon Valley Plaza
3477 Corporate Parkway
Suite #200
Center Valley, PA 18034



24 Hour Emergency Telephone: 908-859-2151
CHEMTREC: 1-800-424-9300

National Response in Canada
CANUTEC: 613-996-6666

Outside U.S. and Canada
Chemtrec: 703-527-3887

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All non-emergency questions should be directed to Customer Service, 1-855-AVANTOR (855-282-6867) for assistance.

POTASSIUM CHROMATE

1. Product Identification

Synonyms: Chromic acid, dipotassium salt; dipotassium chromate; bipotassium chromate

CAS No.: 7789-00-6

Molecular Weight: 194.19

Chemical Formula: K₂CrO₄

Product Codes:

J.T. Baker: 3058

Macron: 6870

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Potassium Chromate	7789-00-6	99 - 100%	Yes

3. Hazards Identification

Emergency Overview

DANGER! STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE A FIRE. CORROSIVE. CAUSES SEVERE BURNS TO EVERY AREA OF CONTACT. HARMFUL IF SWALLOWED OR INHALED. AFFECTS THE RESPIRATORY SYSTEM, LIVER, KIDNEYS, EYES, SKIN AND BLOOD. MAY CAUSE ALLERGIC REACTION. CANCER HAZARD. CAN CAUSE CANCER. Risk of cancer depends on duration and level of exposure.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 3 - Severe (Cancer Causing)

Flammability Rating: 0 - None

Reactivity Rating: 3 - Severe (Oxidizer)

Contact Rating: 3 - Severe (Corrosive)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

Storage Color Code: White (Corrosive)

Potential Health Effects

Inhalation:

Corrosive. Extremely destructive to tissues of the mucous membranes and upper respiratory tract. May cause ulceration and perforation of the nasal septum. Symptoms may include sore throat, coughing, shortness of breath, and labored breathing. May produce pulmonary sensitization or allergic asthma. Higher exposures may cause pulmonary edema.

Ingestion:

Corrosive. Swallowing can cause severe burns of the mouth, throat, and stomach, leading to death. Can cause sore throat, vomiting, diarrhea. May cause violent gastroenteritis, peripheral vascular collapse, dizziness, intense thirst, muscle cramps, shock, coma, abnormal bleeding, fever, liver damage and acute renal failure.

Skin Contact:

Corrosive. Symptoms of redness, pain, and severe burn can occur. Dusts and strong solutions may cause severe irritation. Contact with broken skin may cause ulcers (chrome sores) and absorption, which may cause systemic poisoning, affecting kidney and liver functions. May cause skin sensitization.

Eye Contact:

Corrosive. Contact can cause blurred vision, redness, pain and severe tissue burns. May cause corneal injury or blindness.

Chronic Exposure:

Repeated or prolonged exposure can cause ulceration and perforation of the nasal septum, respiratory irritation, liver and kidney damage and ulceration of the skin. Ulcerations at first may be painless, but may penetrate to the bone producing "chrome holes." Known to be a human carcinogen.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders, asthma, allergies or known sensitization to chromic acid or chromates may be more susceptible to the effects of this material.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion:

If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact:

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Not combustible, but substance is a strong oxidizer and its heat of reaction with reducing agents or combustibles may cause ignition. Releases oxygen, upon decomposition, which enhances combustion.

Explosion:

Contact with oxidizable substances may cause extremely violent combustion. Becomes a possible explosion hazard when shocked, heated, or exposed to hydrazine.

Fire Extinguishing Media:

Flood with large amounts of water. Water spray may be used to keep fire exposed containers cool. Do not allow

water runoff to enter sewers or waterways.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Keep in a tightly closed container. Protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities. Do not store on wooden floors. Wear special protective equipment (Sec. 8) for maintenance break-in or where exposures may exceed established exposure levels. Wash hands, face, forearms and neck when exiting restricted areas. Shower, dispose of outer clothing, change to clean garments at the end of the day. Avoid cross-contamination of street clothes. Wash hands before eating and do not eat, drink, or smoke in workplace. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

- OSHA Permissible Exposure Limit (PEL):

For chromic acid and chromates, as CrO₃ = 0.1 mg/m³ (ceiling)

- ACGIH Threshold Limit Value (TLV):

For water-soluble Cr(VI) compounds, as Cr = 0.05 mg/m³ (TWA), A1 - confirmed human carcinogen.

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Yellow crystals.

Odor:

Odorless.

Solubility:

69.9g/100 g water @ 20C (68F).

Density:

2.73

pH:

Aqueous soln. is alkaline to litmus.

% Volatiles by volume @ 21C (70F):

0

Boiling Point:

No information found.

Melting Point:

975C (1787F)

Vapor Density (Air=1):

6.7

Vapor Pressure (mm Hg):

Zero.

Evaporation Rate (BuAc=1):

No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Burning may produce chrome oxides.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Reducing agents, hydrazine, and flammable materials. Any combustible, organic or other readily oxidizable material (paper, wood, sulfur, aluminum or plastics).

Conditions to Avoid:

Heat, incompatibles.

11. Toxicological Information

Oral rat LD50: 180 mg/kg. Investigated as a tumorigen, mutagen, reproductive effector.

-----\Cancer Lists\-----			
Ingredient	---NTP Carcinogen---		IARC Category
	Known	Anticipated	
Potassium Chromate (7789-00-6)	Yes	No	1

12. Ecological Information

Environmental Fate:

When released into the soil, this material may leach into groundwater. When released into water, this material is not expected to evaporate significantly. This material may bioaccumulate to some extent. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition.

Environmental Toxicity:

Dangerous to the environment. Very toxic to aquatic organisms; may cause long term adverse effects in the aquatic environment.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: RQ, OXIDIZING SOLID, CORROSIVE, N.O.S. (POTASSIUM CHROMATE)

Hazard Class: 5.1, 8

UN/NA: UN3085

Packing Group: III

Information reported for product/size: 375LB

International (Water, I.M.O.)

Proper Shipping Name: OXIDIZING SOLID, CORROSIVE, N.O.S. (POTASSIUM CHROMATE)

Hazard Class: 5.1, 8

UN/NA: UN3085

Packing Group: III

Information reported for product/size: 375LB

15. Regulatory Information

-----\Chemical Inventory Status - Part 1\-----
Ingredient TSCA EC Japan Australia

Potassium Chromate (7789-00-6) Yes Yes Yes Yes

-----\Chemical Inventory Status - Part 2\-----
Ingredient Korea --Canada-- DSL NDSL Phil.

Potassium Chromate (7789-00-6) Yes Yes No Yes

-----\Federal, State & International Regulations - Part 1\-----
-SARA 302- -----SARA 313-----
Ingredient RQ TPQ List Chemical Catg.

Potassium Chromate (7789-00-6) No No No Chromium com

Ingredient	CERCLA	-RCRA- 261.33	-TSCA- 8(d)
Potassium Chromate (7789-00-6)	10	No	No

Chemical Weapons Convention: No TSCA 12(b): Yes CDTA: Yes
SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No
Reactivity: Yes (Pure / Solid)

WARNING:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Australian Hazchem Code: None allocated.

Poison Schedule: S6

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 3 Flammability: 0 Reactivity: 1 Other: **Oxidizer**

Label Hazard Warning:

DANGER! STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE A FIRE. CORROSIVE. CAUSES SEVERE BURNS TO EVERY AREA OF CONTACT. HARMFUL IF SWALLOWED OR INHALED. AFFECTS THE RESPIRATORY SYSTEM, LIVER, KIDNEYS, EYES, SKIN AND BLOOD. MAY CAUSE ALLERGIC REACTION. CANCER HAZARD. CAN CAUSE CANCER. Risk of cancer depends on duration and level of exposure.

Label Precautions:

- Keep from contact with clothing and other combustible materials.
- Do not get in eyes, on skin, or on clothing.
- Do not breathe dust or mist from solutions.
- Keep container closed.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Store in a tightly closed container.
- Do not store near combustible materials.

Label First Aid:

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. In all cases get medical attention immediately.

Product Use:

Laboratory Reagent.

Revision Information:

No Changes.

Disclaimer:

THE INFORMATION PRESENTED IN THIS MATERIAL SAFETY DATA SHEET (MSDS/SDS) WAS PREPARED BY TECHNICAL PERSONNEL BASED ON DATA THAT THEY BELIEVE IN THEIR GOOD FAITH JUDGMENT IS ACCURATE. HOWEVER, THE INFORMATION PROVIDED HEREIN IS PROVIDED "AS IS," AND AVANTOR PERFORMANCE MATERIALS MAKES AND GIVES NO REPRESENTATIONS OR WARRANTIES WHATSOEVER, AND EXPRESSLY DISCLAIMS ALL WARRANTIES REGARDING SUCH INFORMATION AND THE PRODUCT TO WHICH IT RELATES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION, WARRANTIES OF ACCURACY, COMPLETENESS, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY, STABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, COURSE OF PERFORMANCE, OR USAGE OF TRADE.

THIS MSDS/SDS IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT, AND IS NOT INTENDED TO BE COMPREHENSIVE AS TO THE MANNER AND CONDITIONS OF USE, HANDLING, STORAGE, OR DISPOSAL OF THE PRODUCT. INDIVIDUALS RECEIVING THIS MSDS/SDS MUST ALWAYS EXERCISE THEIR OWN INDEPENDENT JUDGMENT IN DETERMINING THE APPROPRIATENESS OF SUCH ISSUES. ACCORDINGLY, AVANTOR PERFORMANCE MATERIALS ASSUMES NO LIABILITY WHATSOEVER FOR THE USE OF OR RELIANCE UPON THIS INFORMATION. NO SUGGESTIONS FOR USE ARE INTENDED AS, AND NOTHING HEREIN SHALL BE CONSTRUED AS, A RECOMMENDATION TO INFRINGE ANY EXISTING PATENTS OR TO VIOLATE ANY FEDERAL, STATE, LOCAL, OR FOREIGN LAWS. AVANTOR PERFORMANCE MATERIALS REMINDS YOU THAT IT IS YOUR LEGAL DUTY TO MAKE ALL INFORMATION IN THIS MSDS/SDS AVAILABLE TO YOUR EMPLOYEES.

Prepared by: Environmental Health & Safety