

Material Safety Data Sheet

91164 Invisible Glass®

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538	Product Name: Invisible Glass® Product Code: 91164 Version Date: 09/12/11 24-hour emergency phone: 1-800-424-9300 [CHEMTREC]
---	---

2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS #	ACGIH TLV	Exposure Limits OSHA PEL	OTHER
Hydrocarbon blend	Mixture	400 ppm Not established	50 ppm (skin) Not established	500 ppm STEL Not established
Hydrocarbon propellant	68-476-86-8	800 ppm	Not established	Not established

3. HAZARDS IDENTIFICATION

POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

- Eye :** May cause eye irritation. Symptoms may include stinging, tearing, and redness. May cause frostbite and irritation.
- Skin :** Skin contact may cause irritation. Symptoms may include redness, discomfort, drying and cracking, or rash. Liquid may cause frostbite.
- Ingestion :** Swallowing small amounts during handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage. Frostbite of the lips and mouth may result from contact with the liquid.
- Inhalation :** Breathing small amounts during handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include: initial Central Nervous System excitation (euphoria, exhilaration, light-headedness) followed by CNS depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects, such as confusion, impaired coordination, coma, and death. May cause nausea, vomiting, coughing and pulmonary irritation.

POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

General Effects: This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. This material (or a component) shortens the time onset or worsens the liver and kidney damage induced by other chemicals. Acute lethal exposures in animal studies of a product component has resulted in congestion of organs including kidney, spleen and lungs. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible kidney effects. mild, reversible liver effects. blood abnormalities.

Cancer Information: THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Skin contact may aggravate an existing dermatitis. Respiratory related chronic illnesses (i.e. asthma, etc.).

HMSI® III* HAZARDOUS WARNINGS:

Health: 2 Flammability: 2 Physical: 0 Personal Protective Equipment: See Section 8

* See www.paint.org/hmsi or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

- Eyes:** Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
- Skin Contact:** In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.
- Ingestion:** Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continue your efforts until help arrives or the victim starts to breathe on his own. Do not leave victim alone. Seek immediate medical attention. Keep the victim warm and quiet.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); liver; kidney; blood forming system;

5. FIRE FIGHTING MEASURES

- Fire and/or Explosion Hazards:** Product is water based material, containing minor amounts of flammable ingredients. This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.
- Fire Fighting Instructions:** Use alcohol foam, water fog, dry chemical, or CO2. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus.
- Aerosol Flame Projection Test:** Non-flammable aerosol, as determined by ASTM D3065-94. However, this product contains components which may be ignited under certain circumstances. Do not use near ignition sources such as sparks or open flames.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. Use with adequate ventilation. If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage. Do not use near ignition sources. Use with adequate ventilation. Protect container against physical damage. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. This material can be harmful or irritating.

Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Empty container may contain residues which are hazardous. Do not store at temperatures above 120 degrees F. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated in "Section 2" of this MSDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded. Ventilation is required to maintain operator exposure below published exposure limits.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: No respiratory protection required under normal conditions of use. A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Vapor Density:	[air = 1] 1.26
Appearance:	Clear Colorless	Evaporation Rate:	0.5-2 (n-Butyl acetate = 1)
Odor:	Mild Alcohol	Solubility in Water:	Not determined
Specific Gravity:	0.96 (H ₂ O=1)	Boiling Point:	Not applicable°F
Vapor Pressure:	53.00 PSIG @ 70°F	pH:	Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Acids. Strong oxidizing agents. Acetaldehyde. Chlorine. Ethylene oxide. Isocyanates. Strong alkalis.

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide.

11. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

12. TRANSPORTATION INFORMATION

Agency	Proper Shipping name	UN Number	Hazard Class	Packing Group
DOT	Consumer commodity	Not applicable	ORM-D	Not applicable
IATA	Flammable liquids, n.o.s. (Contains Isopropanol)	UN1993	3	II

13. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.
No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.
No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.