

SAFETY DATA SHEET

Page 1 of 4

1. IDENTIFICATION

PRODUCT NAME: OVEN & GRILL CLEANER

RECOMMENDED USE: OVEN CLEANER

RESTRICTIONS ON USE: DO NOT USE IN A MANNER INCONSISTENT WITH THE LABEL.

LABEL BRAND: PROPOWER SDS 3126688 CODE 3126688

U S CHEMICAL 316 HART STREET WATERTOWN, WI 53094 USA

MEDICAL EMERGENCY: 1-866-836-8855 USA SPILL EMERGENCY: 1-800-424-9300 USA

PRODUCT INFORMATION: 1-800-558-9566 USA (8 A.M. TO 5 P.M. CST MONDAY TO FRIDAY)

INTERNET ADDRESS: <u>www.uschemical.com</u>

2. HAZARD(S) IDENTIFICATION

CLASSIFICATION: FLAMMABLE AEROSOLS (CATEGORY 1),

SKIN CORROSION (CATEGORY 1B), EYE DAMAGE (CATEGORY 1)

CORROSIVE TO METALS (CATEGORY 1)

LABEL ELEMENTS

SIGNAL WORD: DANGER

PICTOGRAMS: FLAME, CORROSION

HAZARD STATEMENTS: EXTREMELY FLAMMABLE AEROSOL. CAUSES SEVERE SKIN

BURNS AND SERIOUS EYE DAMAGE. MAY BE CORROSIVE TO METALS.

PRECAUTIONARY STATEMENTS: Wear chemical-splash safety goggles, chemical-resistant protective gloves and protective footwear. Avoid contact with eyes, skin and clothing. Do not breathe vapors or mists. Do not eat, drink, or smoke when using this product. Wash hands and affected areas thoroughly after handling. Keep only in original container. Absorb spillage to prevent material damage. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. **IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse. **IF SWALLOWED:** Rinse mouth. **Do NOT** induce vomiting. If conscious, dilute by drinking up to a cupful of milk or water as tolerated. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

START FIRST AID. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

EMERGENCY TELEPHONE: 1-866-836-8855

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50°C (122°F). Store in a well-ventilated place. Store tightly closed only in original corrosive resistant container with resistant inner liner. Store locked up.

Disposal: Dispose of contents in accordance with all federal, state and local applicable laws and regulations.

KEEP OUT OF REACH OF CHILDREN. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

HAZARDS NOT OTHERWISE CLASSIFIED: Not applicable.

3. COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT(S)	CAS#	WEIGHT %
DIETHYLENE GLYCOL MONOBUTYL ETHER	112-34-5	2.5-10.0
SODIUM HYDROXIDE	1310-73-2	2.5-10.0
LIQUEFIED PETROLEUM GAS	68476-86-8	2.5-10.0
EXACT PERCENTAGES ARE BEING WITHHELD AS TRADE SECRET INFORMATION		

EXACT PERCENTAGES ARE BEING WITHHELD AS TRADE SECRET INFURMATION.

STATE RIGHT TO KNOW: SEE SECTION 15 FOR STATE RTK CHEMICAL NAMES IN MIXTURE.

4. FIRST-AID MEASURES

Page 2 of 4

IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING FOR AT LEAST 15 MINUTES. IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER FOR AT LEAST 15 MINUTES. WASH CONTAMINATED CLOTHING BEFORE REUSE. IF SWALLOWED: RINSE MOUTH. Do NOT INDUCE VOMITING. IF CONSCIOUS, DILUTE BY DRINKING UP TO A CUPFUL OF MILK OR WATER AS TOLERATED. IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

START FIRST AID. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

EMERGENCY TELEPHONE: 1-866-836-8855

MOST IMPORTANT SYMPTOMS / EFFECTS: CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY CAUSE BLINDNESS WITHOUT IMMEDIATE FIRST AID. HARMFUL IF SWALLOWED. CAUSES BURNS AND SERIOUS DAMAGE TO MOUTH, THROAT AND STOMACH. CORROSIVE TO ALL BODY TISSUES. MEDICAL CONDITIONS AGGRAVATED: NOT KNOWN.

NOTE TO PHYSICIAN: CALL 1-866-836-8855 FOR EXPOSURE MANAGEMENT ASSISTANCE.

5. FIRE-FIGHTING MEASURES

CHEMICAL HAZARDS: EXTREMELY FLAMMABLE AEROSOL. CORROSIVE.
PRESSURIZED CONTAINER MAY EXPLODE WHEN EXPOSED TO HEAT OR FLAME.
COMBUSTION PRODUCT HAZARDS: OXIDES OF CARBON AND OTHER FUMES.
METHODS: SELECT EXTINGUISHER AND METHODS BASED ON FIRE SIZE AND TYPE.
COOL CONTAINERS EXPOSED TO HEAT WITH WATER SPRAY AND REMOVE
CONTAINER IF NO RISK IS INVOLVED.

EQUIPMENT: WEAR SCBA AND FULL PROTECTIVE GEAR AS CONDITIONS WARRANT. **NFPA RATING:** HEALTH-3/FLAMMABILITY-2/ INSTABILITY-0/SPECIAL HAZARD-N.AP.

SUITABLE EXTINGUISHERS: WATER FOG OR MIST SUITABLE FOR FIRE.

UNSUITABLE EXTINGUISHERS: DO NOT USE WATER JET AS THIS WILL SPREAD FIRE.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: EVACUATE UNPROTECTED PERSONNEL FROM AREA. WEAR PERSONAL PROTECTION INCLUDING RUBBER BOOTS. SEE SECTION 8. VENTILATE AREA IF NEEDED. BE CAREFUL NOT TO SLIP. WASH THOROUGHLY AFTER CLEAN-UP. ENVIRONMENTAL PRECAUTIONS: PREVENT SPILL FROM ENTERING DRAIN, STORM SEWER OR SURFACE WATERWAY. PREVENT WATER AND SOIL CONTAMINATION. CLEAN-UP METHODS: REMOVE ALL IGNITION SOURCES. IF CONTAINERS BEGIN TO LEAK THROUGH PUNCTURE OR DEFECTIVE PACKAGING, ALLOW IT TO DISCHARGE COMPLETELY IN A WELL VENTILATED AREA. SMALL SPILLS MAY BE WIPED UP AND RINSED WITH WATER. FOR LARGER SPILLS, DIKE TO CONTAIN. PUMP TO LABELED CONTAINER OR ABSORB SPILLAGE AND SCOOP UP WITH INERT ABSORBENT MATERIAL. AFTER SPILL COLLECTION, RINSE AREA WITH WATER AND FOLLOW WITH NORMAL CLEAN-UP PROCEDURES.

7. HANDLING AND STORAGE

HANDLING: PRESSURIZED CONTAINER. DO NOT PIERCE OR BURN EVEN AFTER USE. DO NOT USE IF SPRAY BUTTON IS MISSING OR DEFECTIVE. INSTRUCT PERSONNEL ABOUT PROPER USE, HAZARDS, PRECAUTIONS, AND FIRST AID MEASURES. AVOID INHALATION, INGESTION, AND CONTACT WITH EYES, SKIN AND CLOTHING. INTENTIONAL MISUSE BY CONCENTRATING AND INHALING THE PRODUCT CAN BE HARMFUL OR FATAL. USE IN A WELL-VENTILATED PLACE. AVOID SPRAYING TOWARDS FACE. AVOID OVERSPRAY DURING USE. HANDLE CAREFULLY TO AVOID DAMAGING CONTAINER. STORAGE: PRESSURIZED CONTAINER. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C (122°F). STORE IN A WELL-VENTILATED PLACE. STORE LOCKED UP. STORE TIGHTLY CLOSED ONLY IN ORIGINAL CORROSIVE RESISTANT CONTAINER WITH RESISTANT INNER LINER.DO NOT PUNCTURE, INCINERATE OR CRUSH. KEEP AWAY FROM INCOMPATIBLE MATERIALS. KEEP FROM FREEZING. STORE AS LEVEL 1 AEROSOL (NFPA 30B).

Page 3 of 4

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS: DIETHYLENE GLYCOL MONOBUTYL ETHER = 10 PPM TWA (ACGIH) SODIUM HYDROXIDE = 2 MG/M3 CEILING LIMIT (ACGIH), 2 MG/M3 TWA (OSHA)

LIQUEFIED PETROLEUM GAS = 1000 PPM TWA (ACGIH/OSHA)

ENGINEERING CONTROLS: NONE REQUIRED. GENERAL ROOM VENTILATION IS TYPICALLY ADEQUATE.

PERSONAL PROTECTION

EYES: SAFETY GOGGLES (INDIRECT-VENTED OR NON-VENTED) AND AN EYE-WASH STATION.

HANDS: CHEMICAL-RESISTANT PROTECTIVE GLOVES (RUBBER OR NEOPRENE).

RESPIRATORY: SUITABLE RESPIRATOR IF MISTS/VAPORS ARE NOT CONTROLLED BY VENTILATION.
FEET: RUBBER BOOTS DURING SPILL CLEAN-UP AND WHEN EXPOSURE IS POSSIBLE.
BODY: RUBBER FULL-COVER PROTECTIVE CLOTHING WHEN EXPOSURE IS POSSIBLE.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: COLORLESS LIQUID

ODOR: SOLVENT

pH CONCENTRATE: ABOVE 13.0 pH @ 2500 PPM SOLUTION: N.AV.

pH @ USE DILUTION: N.AV.

PHYSICAL STATE: LIQUID+GAS (AEROSOL)

RELATIVE DENSITY (WATER): 1.076 SOLUBILITY (WATER): COMPLETE

VAPOR PRESSURE: 65 to 85 PSIG @70°F

VAPOR DENSITY: N. AV. VISCOSITY: NON-VISCOUS

AUTO-IGNITION TEMPERATURE: N.AV. DECOMPOSITION TEMPERATURE: N.AV. EXPLOSIVE LIMITS (LEL/UEL): NONE

EVAPORATION RATE: N.AV.

FLAMMABILITY (SOLID, GAS): N.AP.

FLASH POINT: -156°F(-104.4°C) LPG ESTIMATED

INITIAL BOILING POINT/RANGE: N.AV. MELTING POINT/FREEZING POINT: N.AV.

ODOR THRESHOLD: N.AV.

PARTITION COEFF. (N-OCTANOL/WATER): N.AV. OTHER: *LIQUID AND GAS IN AEROSOL CAN

AEROSOL SPRAY ENCLOSED SPACE DEFLAGRATION DENSITY: NOT AVAILABLE

AEROSOL SPRAY IGNITION DISTANCE: NOT AVAILABLE

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE.

REACTIVITY: NO HAZARD.

POSSIBILITY OF HAZARDOUS REACTIONS: NONE KNOWN. WILL NOT POLYMERIZE. CONDITIONS TO AVOID: DO NOT STORE ABOVE 49°C OR 120°F. KEEP AWAY FROM HEAT, DIRECT SUNLIGHT, OPEN FLAMES OR SPARKS. AVOID SPRAYING ON HOT SURFACES. FIRE, INTENSE HEAT OR DROPPING MAY CAUSE VIOLENT RUPTURE OF AEROSOL CAN. MATERIALS TO AVOID: METALS, ACIDS AND OTHER CLEANERS. MIX ONLY WITH WATER. HAZARDOUS DECOMPOSITION PRODUCTS: NONE UNDER NORMAL CONDITIONS.

11. TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE: EYES, SKIN, INGESTION, INHALATION.

INFORMATION ON ROUTES OF EXPOSURE: NO LC50/LD50 TEST DATA ON MIXTURE.

ACUTE EFFECTS /SYMPTOMS: CORROSIVE TO ALL BODY TISSUES.

EYES: CAUSES SERIOUS EYE DAMAGE. MAY CAUSE PAIN, REDNESS AND WATERING.

SKIN: CAUSES SEVERE SKIN BURNS. MAY CAUSE DELAYED PAIN, REDNESS AND BLISTERING.

INGESTION: CAUSES BURNS AND SERIOUS DAMAGE TO MOUTH, THROAT AND STOMACH.

INHALATION: MAY CAUSE CORROSIVE EFFECTS TO NOSE, THROAT, AND RESPIRATORY SYSTEM.

CHRONIC / OTHER EFFECTS: NO REPORTABLE GERM CELL MUTAGENS, SKIN SENSITIZERS, RESPIRATORY SENSITIZERS. REPRODUCTIVE TOXINS OR ASPIRATION HAZARDS.

SPECIFIC TARGET ORGANS (SINGLE/REPEATED): NONE KNOWN.

NUMERICAL MEASURES OF TOXICITY: ATEMIX (ORAL-RAT) = ABOVE 2000 MG / KG

CARCINOGENS: NO REPORTABLE ACGIH, IARC, NTP, OR OSHA CARCINOGENS.

12. ECOLOGICAL INFORMATION

Page 4 of 4

ECOTOXICITY / CHEMICAL FATE: NOT AVAILABLE.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: IGNITABLE AND CORROSIVE WASTE (RCRA CLASS D001, D002). DISPOSE OF CONTENTS IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL APPLICABLE LAWS AND REGULATIONS. CONSULT STATE AND LOCAL AUTHORITIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE. MANAGE CHEMICAL WASTES THROUGH AN APPROVED WASTE TREATMENT FACILITY. PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT INCINERATE. WHEN CONTENTS ARE DEPLETED CONTINUE TO DEPRESS BUTTON UNTIL ALL GAS IS EXPELLED. AEROSOL CYLINDER IS NOT REFILLABLE. GIVE TO A DISPOSAL SERVICE EQUIPPED TO SAFELY DISPOSE OF PRESSURIZED CONTAINERS. PLEASE RECYCLE PACKAGING WHENEVER POSSIBLE.

14. TRANSPORT INFORMATION

DOT / IMDG / TDG: UN1950, AEROSOLS, 2.1, (8) LTD. QTY.

15. REGULATORY INFORMATION

EPA CERCLA RQ: NO EPA REGISTERED: NO OSHA HAZARDOUS: YES

PHOSPHORUS CONTENT: 0.00%

PROPOSITION 65: NO

SARA 311/312 HAZARDS: ACUTE, FIRE, PRESSURE

SARA 313 CHEMICALS: NO

STATE RIGHT TO KNOW: WATER/7732-18-5,

DIETHYLENE GLYCOL MONOBUTYL ETHER/112-34-5, SODIUM HYDROXIDE/1310-73-2.

LIQUEFIED PETROLEUM GAS/68476-86-8

TSCA INVENTORY STATUS: ALL COMPONENTS ARE LISTED ON THE INVENTORY. VOC: 5.00% CALCULATION METHOD USED IS BASED ON CALIFORNIA ARB STANDARD.

16. OTHER INFORMATION

PREPARATION DATE: 1-9-15 **PREPARED BY:** RC **ABBREVIATIONS:** N.AV. = NOT AVAILABLE **REVISED SECTION:** 16 N.AP. = NOT APPLICABLE

NOTICE TO READER

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED WITHIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE FOR EVALUATING ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.