

**SPECTREM 2 LIMESTONE (CDN) 30CTG**

Version 2.0

Print Date 08/13/2012

REVISION DATE: 07/08/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : SPECTREM 2 LIMESTONE (CDN) 30CTG
Product code : 947805 323

COMPANY : Tremco Incorporated
3735 Green Road
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Light Gray. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.
Eyes : Direct contact may cause moderate irritation.
Ingestion : May cause irritation to the mouth, throat and stomach.
Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Possible skin sensitization. As a by-product of curing up to 4% Methyl Ethyl Ketoxime (MEKO) may be released within product. Repeated and prolonged exposure to MEKO can cause allergic skin reaction. It may adversely affect the blood, (methemoglobinemia and anemia). Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Organosilane may cause liver injury with fibrosis after repeated and prolonged overexposure. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Blood, Lung, Liver, Kidney

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Calcium Carbonate (Limestone)	1317-65-3	40.0 - 70.0
Silicone polymer	NJ TSRN# 51721300-5110P	40.0 - 70.0
Polydimethylsiloxane, trimethyl endcap	63148-62-9	7.0 - 13.0
Amorphous silica	7631-86-9	3.0 - 7.0
Oximino Silane	22984-54-9	1.0 - 5.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <1.0

SPECTREM 2 LIMESTONE (CDN) 30CTG

Version 2.0

Print Date 08/13/2012

REVISION DATE: 07/08/2012

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- | | | |
|--------------|---|---|
| Inhalation | : | Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. |
| Eye contact | : | Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately. |
| Skin contact | : | Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately. |
| Ingestion | : | Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately. |

SECTION 5 - FIRE FIGHTING MEASURES

- | | | |
|---------------------------------------|---|---|
| Flash point | : | Not available. |
| Method | : | Not available. |
| Burning rate | : | Non-flammable solid |
| Lower explosion limit | : | Not available. |
| Upper explosion limit | : | Not available. |
| Autoignition temperature | : | Not available. |
| Extinguishing media | : | If water fog is ineffective, use carbon dioxide, dry chemical or foam. |
| Hazardous combustion products | : | Smoke, fumes. Carbon monoxide and carbon dioxide can form. Silicon oxides and trace amounts of MEKO. |
| Protective equipment for firefighters | : | Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). |
| Fire and explosion conditions | : | This product not expected to ignite under normal conditions of use. |

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Keep out of water courses. Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Store in sealed containers in a cool, dry, ventilated warehouse location.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

SPECTREM 2 LIMESTONE (CDN) 30CTG

Version 2.0

Print Date 08/13/2012

REVISION DATE: 07/08/2012

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator, as directed by the manufacturer, when the airborne contaminant level(s) exceed the exposure limits indicated on the MSDS.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : General ventilation is sufficient.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL: OSHA PEL: ACGIH TWA: ACGIH TWA: OSHA TWA: OSHA TWA:	5 mg/m3 15 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Amorphous silica	7631-86-9	ACGIH TWA: ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA:	3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3 0.8 mg/m3	Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Non-sag gunnable paste
- Color : Light Gray
- Odor : Oxime
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Specific Gravity : 1.34

SPECTREM 2 LIMESTONE (CDN) 30CTG

Version 2.0

Print Date 08/13/2012

REVISION DATE: 07/08/2012

% Volatile Weight : 0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Strong acids.Strong bases.Alcohols.Water or moisture and oxidizing agents.

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Amorphous silica, CAS-No.: 7631-86-9

Acute oral toxicity (LD-50 oral) 22,500 mg/kg (Rat) 15,000 mg/kg (Mouse)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA**CFR / DOT:**

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SPECTREM 2 LIMESTONE (CDN) 30CTG

Version 2.0

Print Date 08/13/2012

REVISION DATE: 07/08/2012

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :

Calcium Carbonate (Limestone)	1317-65-3
Amorphous silica	7631-86-9
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

OSHA Status: Considered : Irritant
hazardous based on the
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 8 g/l
exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components	Calcium Carbonate (Limestone)	1317-65-3
	Amorphous silica	7631-86-9

Penn RTK Components	Calcium Carbonate (Limestone)	1317-65-3
	Silicone polymer	NJ TSRN# 51721300-5110P
	Polydimethylsiloxane, trimethyl endcap	63148-62-9
	Amorphous silica	7631-86-9

NJ RTK Components	Calcium Carbonate (Limestone)	1317-65-3
	Silicone polymer	NJ TSRN# 51721300-5110P
	Polydimethylsiloxane, trimethyl endcap	63148-62-9
	Amorphous silica	7631-86-9
	Oximino Silane	22984-54-9
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION**HMIS Rating :**

Health	2
Flammability	1
Reactivity	0
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe



SPECTREM 2 LIMESTONE (CDN) 30CTG

Version 2.0

Print Date 08/13/2012

REVISION DATE: 07/08/2012

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System