

		Page: 1
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Pyroil™ GAS TREAT
GAS TREATMENT

Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Personal care

Details of the supplier of the safety data sheet Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	Emergency telephone number CHEMTREC DIRECT 1-800-424-9300 Product Information 1-844-696-4836
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Skin irritation : Category 2

Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :





Signal Word : Danger

Hazard Statements : Flammable liquid and vapor.
May be fatal if swallowed and enters airways.
Causes skin irritation.

		Page: 2
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

May cause drowsiness or dizziness.

Precautionary Statements

: Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
 Wash skin thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 Do NOT induce vomiting.
 If skin irritation occurs: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
KEROSENE	8008-20-6	Flam. Liq. 3; H226 Skin Irrit. 2; H315	97.22

		Page: 3
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT PYAG12P		Version: 1.1

		STOT SE 3; H336 Asp. Tox. 1; H304	
--	--	--------------------------------------	--

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Call a POISON CENTRE or doctor/physician if exposed or you feel unwell. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	: Move to fresh air. If unconscious place in recovery position and seek medical advice. Consult a physician after significant exposure.
In case of skin contact	: Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Obtain medical attention. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) Lung irritation

		Page: 4
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

confusion
 irregular heartbeat
 Convulsions
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 May cause drowsiness or dizziness.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Aldehydes
 carbon dioxide and carbon monoxide
 Hydrocarbons
 Nitrogen oxides (NO_x)
 sulfur oxides
- Specific extinguishing methods :

 Product is compatible with standard fire-fighting agents.
- Further information : Do not use a solid water stream as it may scatter and spread fire.
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
 Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

		Page: 5
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Evacuate personnel to safe areas.
Remove all sources of ignition.
Use personal protective equipment.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |
| Other information | : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet. |

SECTION 7. HANDLING AND STORAGE

- | | |
|-----------------------------|---|
| Advice on safe handling | : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations. |
| Conditions for safe storage | : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
Electrical installations / working materials must comply with the technological safety standards. |

NiTEO PRODUCTS		Page: 6
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
KEROSENE	8008-20-6	TWA	200 mg/m3 Non-aerosol (as total hydrocarbon vapor)	ACGIH
		REL	100 mg/m3	NIOSH/GUID E

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Material : nitrile rubber

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Flame-resistant clothing

		Page: 7
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Discard gloves that show tears, pinholes, or signs of wear.
 Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : yellow

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available
 No data available

Boiling point/boiling range : > 293 °F / 145 °C

Flash point : 120.00 °F / 48.89 °C
 Calculated Flash Point

Evaporation rate : < 1

Flammability (solid, gas) : No data available

Upper explosion limit : 5 %(V)
 Calculated Explosive Limit

Lower explosion limit : 0.7 %(V)
 Calculated Explosive Limit

Vapour pressure : 0.63994 hPa (20 °C)
 Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.8051 g/cm³ (15.56 °C)

Solubility(ies)
 Water solubility : insoluble

		Page: 8
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons
Nitrogen oxides (NOx)
Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

KEROSENE:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 420

		Page: 9
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

Acute inhalation toxicity : LC 50 (Rat): > 5.28 mg/l
 Exposure time: 4 h
 Test atmosphere: vapour
 Method: OECD Test Guideline 403
 Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

KEROSENE:

Result: Irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

KEROSENE:

Result: Slightly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

KEROSENE:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

		Page: 10
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

Components:

KEROSENE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

KEROSENE:

Remarks: Skin

Remarks: Central nervous system

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

KEROSENE:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Water flea (Daphnia magna)): 1.4 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 1 - 3 mg/l
Exposure time: 72 h

		Page: 11
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : (Water flea (Daphnia magna)): 0.89 mg/l
Exposure time: 21 d
End point: Reproduction Test
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 211

Persistence and degradability

Components:

KEROSENE:

Biodegradability : Biodegradation: 58.6 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1993	FLAMMABLE LIQUID, N.O.S. (KEROSENE)	3	III	LIMITED QUANTITY

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1993	Flammable liquid, n.o.s. (KEROSENE)	3	III	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1993	Flammable liquid, n.o.s. (KEROSENE)	3	III	

NiTEO PRODUCTS		Page: 13
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1993	LIQUIDO INFLAMABLE, N.E.P. 3 (KEROSENE)	III
----	------	--	-----

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
NAPHTHALENE	91-20-3	100	214132.762313

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard

SARA 313 Component(s) : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know
KEROSENE

8008-20-6 90.00 -
100.00 %

New Jersey Right To Know
KEROSENE

8008-20-6 90.00 -
100.00 %

POLYMER

Not Assigned 1.00 - 5.00 %

California Prop 65 Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AICS : On the inventory, or in compliance with the inventory

		Page: 14
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

NZIOC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2015

NFPA:	HMIS III:						
Flammability  Health Instability Special hazard.	<table border="1"> <tr> <td>HEALTH</td><td>2</td></tr> <tr> <td>FLAMMABILITY</td><td>2</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> 0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic	HEALTH	2	FLAMMABILITY	2	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	2						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class II

Full text of H-Statements referred to under sections 2 and 3.

H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet

		Page: 15
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

Internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.
Cefic, the European Chemical Industry Council.
ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health

		Page: 16
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 12/8/2015
		SDS Number: R0326703
Pyroil™ GAS TREAT GAS TREATMENT		Version: 1.1
PYAG12P		

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System