

1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 112
Revision Date: 4/20/2012
Supersedes Date: 05/04/2009

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200


Product Name: LIQUID SOLDER FLUX

SECTION 1- PRODUCT AND COMPANY IDENTIFICATION

Product Type: Solder Flux
Product Name: **LIQUID SOLDER FLUX**
Part Number(s): **10-4202**
10-4216

Emergency Contact: **Chemtrec**
Phone: **(800) 424-9300**

Common Name: Liquid Solder Flux
Chemical Name: Rosin Solder Flux
Family Usage: Soldering Flux for Electrical or Electronic Applications
Description: Mixture of the substances listed below with non-hazardous additions.
GHS Class: Highly Flammable liquid and vapour



This product has to be labeled due to the calculation procedure of international guidelines. Has a narcotizing effect. Highly flammable. Irritating to eyes. May cause sensitization by skin contact. Vapors may cause drowsiness and dizziness.

Least 0
Slight 1
Moderate 2
High 3
Extreme 4
Gloves, Safety Glasses B

HMIS	
Health Hazard	1
Fire Hazard	3
Reactivity	0
Personal Protection	x

* Chronic Health Effects

Information pertaining to particular dangers for man and environment:

Personal Protective Equipment



Chemical Splash Goggles
Safety Glasses
Protective Gloves

WHMIS Pictograms



Flammable D2B Toxic

GHS Pictograms



Highly flammable liquid and vapour

DOT Pictograms



Flammable Liquid



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 112
Revision Date: 4/20/2012
Supersedes Date: 05/04/2009

MATERIAL SAFETY DATA SHEET

Product Name: LIQUID SOLDER FLUX

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Gum rosin	8050-09-7	30 - 60 by weight	
Isopropyl alcohol	67-63-0	30 - 60 by weight	

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:	DANGER! Flammable. Potential Sensitizer Flux fumes during soldering may cause irritation and damage of mucous membranes and respiratory system.
Route of Exposure:	Eyes. Skin. Inhalation. Ingestion.
Eye:	Eye contact with product or vapors may result in irritation, redness, and blurred vision. Smoke during soldering can cause eye irritation.
Skin:	May cause irritation. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
Inhalation:	Inhalation of vapors, fumes or mists of the product may be irritating to the respiratory system. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.
Ingestion:	May be harmful if swallowed. May cause vomiting.
Chronic Health Effects:	Prolonged or repeated contact may cause skin irritation. Repeated or prolonged inhalation may cause toxic effects.
Signs/Symptoms:	Overexposure may cause headaches and dizziness.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	None generally recognized.

SECTION 4 - FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 112
Revision Date: 4/20/2012
Supersedes Date: 05/04/2009

MATERIAL SAFETY DATA SHEET

Product Name: LIQUID SOLDER FLUX

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point:	18 °C (64 °F)
Auto Ignition Temperature:	425.0 °C (797 °F)
Lower Flammable/Explosive Limit:	2.0 % by volume
Upper Flammable/Explosive Limit:	12.0 % by volume
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Unsuitable Media:	Do not use a solid water stream as it may scatter and spread fire.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Hazardous Combustion Byproducts:	Oxides of carbon, oxides of nitrogen, aliphatic aldehydes, and other organic substances may be formed during combustion..

NFPA Ratings:

NFPA Health:	1
NFPA Flammability:	3
NFPA Reactivity:	0

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Avoid breathing vapor, aerosol or mist. Avoid contact with skin, eyes and clothing.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Methods for containment:	Contain spills with an inert absorbent material such as soil, sand or oil dry.
Methods for cleanup:	Remove all sources of ignition. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Place into a suitable container for disposal.



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 112
Revision Date: 4/20/2012
Supersedes Date: 05/04/2009

MATERIAL SAFETY DATA SHEET

Product Name: LIQUID SOLDER FLUX

SECTION 7 - HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor and fumes. Use only in accordance with directions. To reduce potential for static discharge, bond and ground containers when transferring material.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, direct sunlight, and incompatible substances. Keep container tightly closed when not in use.
Special Handling Procedures:	DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container.
Hygiene Practices:	Wash thoroughly after handling. Avoid inhaling vapors, mists, or fumes.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Tightly fitting safety goggles. Wear a face shield also when splash hazards exist
Hand Protection Description:	Wear appropriate protective gloves. Consult glove manufacturer's data for permeability data. Nitrile rubber or natural rubber gloves are recommended.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 112
Revision Date: 4/20/2012
Supersedes Date: 05/04/2009

MATERIAL SAFETY DATA SHEET

Product Name: LIQUID SOLDER FLUX

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES (CONTINUED)

Gum rosin :

Guideline ACGIH: Sensitizer.: Sen

Isopropyl alcohol :

Guideline ACGIH: TLV-STEL: 400 ppm
TLV-STEL: 400 ppm

Guideline OSHA: PEL-TWA: 400 ppm

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid.
Color: Amber
Odor: Alcohol-like
Boiling Point: 82 °C (180 °F)
Melting Point: Not determined.
Density: 0.880 g/cm³ @ 20°C (68°F)
Vapor Pressure: 33 mmHg @ 20°C (68°F)
Flash Point: 18 °C (64 °F)
Auto Ignition Temperature: 425.0 °C (797 °F)

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.
Hazardous Polymerization: Not reported.
Conditions to Avoid: Keep away from heat, ignition sources and incompatible materials.
Incompatible Materials: Oxidizing agents. Strong acids and alkalis.
Special Decomposition Products: When heated to soldering temperatures, the solvents are evaporated and rosin may be thermally degraded to liberate aliphatic aldehydes and acids.



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 112
Revision Date: 4/20/2012
Supersedes Date: 05/04/2009

MATERIAL SAFETY DATA SHEET

Product Name: LIQUID SOLDER FLUX

SECTION 11 - TOXICOLOGICAL INFORMATION

Gum rosin :

RTECS Number: VL0480000

Inhalation: Inhalation. - Rat LC50: 110 mg/m³ [Behavioral - somnolence (general depressed activity) Cardiac - pulse rate Lungs, Thorax, or Respiration - respiratory depression] (RTECS)

Ingestion: Oral - Mouse LD50: 2.2 mg/kg [Behavioral - somnolence (general depressed activity) Cardiac - pulse rate Lungs, Thorax, or Respiration - respiratory depression]
Oral - Rat LD50: 3.0 mg/kg [Brain and Coverings - other degenerative changes Liver - other changes Biochemical - Metabolism (Intermediary) - other] (RTECS)

Isopropyl alcohol :

RTECS Number: NT8050000

Eye: Eye - Rabbit Standard Draize test: 100 mg
Eye - Rabbit Standard Draize test: 10 mg
Eye - Rabbit Standard Draize test: 100 mg/24H (RTECS)

Skin: Administration onto the skin - Rabbit Standard Draize test: 500 mg
Administration onto the skin - Rabbit LD50: 12800 mg/kg [Details of toxic effects not reported other than lethal dose value.] (RTECS)

Inhalation: Inhalation. - Rat LC50: 16000 ppm/8H [Details of toxic effects not reported other than lethal dose value.]
Inhalation. - Mouse LC50: 53000 mg/m³ [Behavioral - general anesthetic Lungs, Thorax, or Respiration - other changes]
Inhalation. - Rat LC50: 72600 mg/m³ [Behavioral - general anesthetic Lungs, Thorax, or Respiration - other changes] (RTECS)

Ingestion: Oral - Rat LD50: 5045 mg/kg [Behavioral - altered sleep time (including change in righting reflex) Behavioral - somnolence (general depressed activity)]
Oral - Mouse LD50: 3600 mg/kg [Behavioral - altered sleep time (including change in righting reflex) Behavioral - somnolence (general depressed activity)]
Oral - Mouse LD50: 3600 mg/kg [Behavioral - general anesthetic]
Oral - Rat LD50: 5000 mg/kg [Behavioral - general anesthetic] (RTECS)



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 112
Revision Date: 4/20/2012
Supersedes Date: 05/04/2009

MATERIAL SAFETY DATA SHEET

Product Name: LIQUID SOLDER FLUX

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.
Environmental Fate: No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Isopropanol, mixture
DOT UN Number: UN1219
DOT Hazard Class: 3
DOT Packing Group: II
Label: 3 Flammable Liquids
Description: Soldering Flux
IATA Shipping Name: Isopropanol, mixture
IATA UN Number: UN1219
IATA Hazard Class: 3
IATA Packing Group: II
IMDG UN Number : UN1219
IMDG Shipping Name : Isopropanol, mixture
IMDG Hazard Class : 3
IMDG Packing Group : II
RID UN Number : UN1219
RID Shipping Name : Isopropanol, mixture
RID Hazard Class : 3
RID Packing Group : II



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 112
Revision Date: 4/20/2012
Supersedes Date: 05/04/2009

MATERIAL SAFETY DATA SHEET

Product Name: LIQUID SOLDER FLUX

SECTION 15 - REGULATORY INFORMATION

Canada Reg. Status:	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.
Canada WHMIS:	Controlled - Class: B2 Flammable Liquid Controlled - Class: D2B Toxic
<u>Gum rosin :</u>	
TSCA Inventory Status:	Listed
Canada DSL:	Listed
<u>Isopropyl alcohol :</u>	
TSCA Inventory Status:	Listed
Canada DSL:	Listed

WHMIS Pictograms



SECTION 16 - ADDITIONAL INFORMATION

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.